

LSS650 WATER COOLING CONVEYER

LSS650 水冷式冷却输送机



LSS650 WATER COOLING CONVEYER

LSS650 水冷式冷却输送机

水冷式冷却输送机是专为解决胶坯粘连、变形而设计的预成型机配套辅机。通过冷却水或冷却溶液使胶坯降温，再经过强制风冷，使胶坯干燥、稳定。该机特点是全程不锈钢网链可调控运行速度，配合精密预成型机的所有切割速度。

The water cooling conveyor is an auxiliary machine of the precision preformer to avoid stickiness and deformation of the rubber blanks. After cooling down with cooling water or cooling solution, and then with forcible cooling wind, the rubber blanks will become dry and stable. The feature of the machine is the running speed can be adjusted by the stainless steel net curtain during the whole process, to go with all the cutting speeds of the preformer.

LSS650 Water Cooling Conveyor Technical Parameter

LSS650 冷却输送机技术参数

| 项目名称 / Items | 单位 / Unit | LSS650 |
|---|-------------------|----------------|
| 斜面输送 (全部采用不锈钢材料) Sloping conveying(stainless steel) | | |
| 输送宽度 Conveying width | mm | 450 |
| 料坯浸水距离 Distance of blank conveying (in water) | mm | 700 |
| 输送速度 Conveying speed | m/min | 8.3 |
| 冷却风量 Volume of cooling wind | m ³ /h | 1620 |
| 水平输送 Horizontal conveying | | |
| 输送宽度 Conveying width | mm | 380 |
| 水平输送速度 (可调) Conveying speed (Adjustable) | m/min | 1.6 ~ 3.2 |
| 层次 Layer | | 3 |
| 水箱尺寸 (L×W×H) Water tank dimension | m | 1.46×0.8×0.27 |
| 冷却风量 Volume of cooling wind | m ³ /h | 10320 |
| 外形尺寸 (L×W×H) External dimension | m | 5.35×0.75×1.84 |
| 总功率 Total power | KW | 1.8 |
| 重量 Weight | t | 1.2 |